



Technical data sheet

## **CINERGI 1060**

### **Sheet fed free flow varnish**

#### **IMPORTANT CHARACTERISTICS:**

**Cinergi 1060** is a tack stable varnish that maintains body in an ink at high shear temperatures. The lithographic properties of **Cinergi 1060** assure high print performance in both short and long press runs. **Cinergi 1060** exhibits excellent water balance properties. It is recommended to combine together with gel varnish of **Cinergi 1061** in a typical sheetfed ink formula.

#### **APPLICATIONS:**

- Sheetfed
- Wetting varnishes

#### **BENEFITS:**

- High gloss
- Fast setting
- Good flow
- Low misting
- Excellent water balance
- Distillate 290-340 °C

#### **Typical Properties**

<b>Property</b>	<b>Value</b>	<b>Unit</b>	<b>Test Method / Standard</b>
Tack	11		400rpm, 30', 90 °F
Viscosity	35,000	cp	Emila, 25 °C

Updated 5/18/11 TM

**Former name :CXV-1060**

® and ™ Licensed trademarks of Lawter, Inc.

#### **DISCLAIMER**

The information provided herein was believed by Lawter, Inc. ("Lawter") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter's terms and conditions of sale. LAWTER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter's specifications. Nothing contained herein constitutes an offer for the sale of any product.