



Technical Data Sheet

## Cinergi™ 2035 A Free Flow Quickset Varnish

### IMPORTANT CHARACTERISTICS:

**Cinergi™ 2035 A** is a 100% non-volatile, low tack, quickset free flow vehicle designed primarily to adjust flow and tack in high solids ink systems. Based on elastic resin technologies, **Cinergi 2035 A** will increase flow, transfer and leveling, resulting in higher gloss, while not adversely affecting set speed.

When used with other **Cinergi** lithographic vehicle products, superior ink performance on the press can be realized.

### APPLICATIONS:

- Sheetfed inks
- Increased flow, transfer and leveling
- High gloss
- Tack and flow reducer

### BENEFITS:

- High solids sheetfed

### Typical Properties

Properties	Value	Test Method / Standard
Viscosity:	225	Gardner Bubble Tube @100°F (Line:Line, sec.) Method PP-QC-142
Inkometer Tack:	12	400 rpm, 1 min. @ 90°F Method PP-QC-101
% Non-Volatile:	100	Method PP-QC-105
Drying Oil Type:	Mixed Vegetable	

Updated 2/10/2011 JGC

For more information, please contact your sales or technical representative.

® and ™ Licensed trademarks of Lawter, Inc.

### DISCLAIMER

The information provided herein was believed by Lawter, Inc. ("Lawter") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter's terms and conditions of sale. LAWTER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter's specifications. Nothing contained herein constitutes an offer for the sale of any product.