



Technical Data Sheet

Cinergi™ 80 A Quickset Varnish

IMPORTANT CHARACTERISTICS:

Cinergi™ 80 A is a high solids quickset free flow vehicle based on internally highly structured resin systems. This feature provides for fast setting, greater compatibility and synergy with a broader range of flush color systems. **Cinergi 80 A** is an excellent letdown/free flow companion vehicle for **Cinergi** gelled systems.

APPLICATIONS:

- Sheetfed inks

BENEFITS:

- Fast setting

Typical Properties

Properties	Value	Test Method / Standard
Viscosity:	150	GH Bubble Tube @ 100°F, E-E, sec Method PP-QC-141
Inkometer Tack:	8	@ 400 rpm, 1 min., 90°F Method PP-QC-101
% Non-Volatile:	80	Method PP-QC-105
Color:	14 max	Method PP-QC-181
Solvent Boiling Range:	560-710°F	
Weight/Gallon:	7.9 lbs	BAX-QC-130

Updated 2/10/2011 JGC

For more information, please contact your sales or technical representative.

® and ™ Licensed trademarks of Lawter, Inc.

DISCLAIMER

The information provided herein was believed by Lawter, Inc. ("Lawter") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter's terms and conditions of sale. LAWTER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter's specifications. Nothing contained herein constitutes an offer for the sale of any product.