

Flex-Rez™ 1155AS A Polyamide Resin

Description: (An overview of all products is available on request.)	Alcohol soluble polyamide resin 100% solids	
Composition:	Polyamide resin	
Application Field:	Flexo/gravure inks for foils and plastics Coatings and overprint varnishes Cold seal release lacquer	
Special Properties and advantages:	Good gel resistance Pigment wetting High gloss Adhesion Film forming Grease, oil, lard, alkali and water resistance	
Recommendations: (An overview of starting point formulations is available on request.)	Compatible with maleic and phenolic resins NC-compatible	Alcohol soluble
Typical Properties: (Test methods available on request.) KOH/g)	Melting point (R&B, °C) Max 6 Amine value (mg KOH/g) Viscosity (50% NV 95% Ethanol, GH 25 °C) Colour Viscosity 50% in Ethanol, 23 °C Ford #4 DIN #4 Shell #5 Zahn #3 Dilution in Ethanol (% NV)	115 Acid value (mg Max 6 D Max 10 39" 34" 20" 19" 31
Former Name:	P-1155	

Updated 2/10/2011 JGC

For more information, please contact your sales or technical representative.

® and ™ Licensed trademarks of Lawter, Inc.

DISCLAIMER

The information provided herein was believed by Lawter, Inc. ("Lawter") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter's terms and conditions of sale. LAWTER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter's specifications. Nothing contained herein constitutes an offer for the sale of any product.