



Technical Data Sheet

Miraglaze™ 2540 A Sheetfed Overprint Varnish

IMPORTANT CHARACTERISTICS:

Miraglaze™ 2540 A is an economical workhorse “press ready” overprint varnish. This product has excellent press stability and “stay open” properties on the press, which is helpful during often interrupted press runs.

Miraglaze 2540 A contains waxes and driers that may be wet or dry trapped. **Miraglaze 2540 A** exhibits high gloss with good rub resistance and considered non-imprintable.

APPLICATIONS:

- Overprints
 - Non-imprintable
 - Wet and dry trap

BENEFITS:

- Excellent tack stability
- “Stay open” properties
- Free-flow

Typical Properties

Properties	Value	Test Method / Standard
Inkometer Tack:	7.5	1200 rpm, 1 min. @ 90°F Method PP-QC-101
% Non-Volatile:	70	Method PP-QC-105
Solvent Type:	Hydrotreated	
Solvent Boiling Range:	515-586°F	
Weight/Gallon:	7.7 lbs	Method PP-QC-130

Updated 2/10/2011 JGC

For more information, please contact your sales or technical representative.

® and ™ Licensed trademarks of Lawter, Inc.

DISCLAIMER

The information provided herein was believed by Lawter, Inc. (“Lawter”) to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter’s terms and conditions of sale. LAWTER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter’s specifications. Nothing contained herein constitutes an offer for the sale of any product.