

Stirinol™ 350 A Coatable Polyethylene/PTFE Heatset Compound

IMPORTANT CHARACTERISTICS:

Stirinol™ 350 A is a UV and aqueous coatable, high performance polyethylene/PTFE compound formulated to exhibit exceptional rub resistance, gloss retention, and slip in heatset inks. **Stirinol 350 A** resists re-crystallization at ink processing temperature. The recommended usage level is 4 to 7%.

APPLICATIONS:

- Heatset inks

BENEFITS:

- Excellent rub resistance and slip
- UV and aqueous coatable, imprintable
- Minimal effect on gloss.
- Resistant to re-crystallization

Typical Properties

Properties	Value	Test Method / Standard
Grind:	N-0	NPIRI Gage units, (10% in ink) Method: BAX-QC-201
Peppering:	N-5	NPIRI Gage units, (10% in ink) Method: BAX-QC-201
Color:	white	Compared to standard
Body:	Soft Paste	Compared to standard
% Non-volatile:	45%	Method: BAX-QC-195
Solvent Boiling Range:	475-515°F	
Weight/Gallon:	7.3 lbs	Method: BAX-QC-130

Updated 02/11/11 TD

For more information, please contact your sales or technical representative.

® and ™ Licensed trademarks of Lawter, Inc.

DISCLAIMER

The information provided herein was believed by Lawter, Inc. ("Lawter") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter's terms and conditions of sale. LAWTER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter's specifications. Nothing contained herein constitutes an offer for the sale of any product.