



Technical Data Sheet

DECOTHERM™ 295 E

Preliminary datasheet

**MO free version of Decotherm 290
Polyester for Metal deco 2-piece can**

IMPORTANT CHARACTERISTICS:

Decotherm™ 295 E is used for metal deco inks printed with spindle printing (dry offset) for 2 piece can.

Decotherm™ 295 E reduces misting significantly at low tack levels.

Decotherm™ 295 E will accept a water based coating.

Decotherm™ 295 E exhibits better color retention and maintains a non-Newtonian rheology.

APPLICATIONS:

- Spindle printing, dry offset
- Metal deco 2-piece can
- Colored inks
- White inks
- Acid catalyzed curing system

BENEFITS:

- Low misting and low tack
- Very good transfer on high speed presses
- Very good overcoatable with water based coatings
- Good adhesion on metals
- Good hardness

Typical Properties

Property	Value	Unit	Test Method / Standard
Acid Value	35	mg KOH / g	Titration LIMR1
Viscosity	110	Pa.s	Viscosity at 23°C at 25 sec ⁻¹ LIMV2

Updated February 22, 2013 by AdK

® and ™ Licensed trademarks of Lawter, Inc.

DISCLAIMER

The information provided herein was believed by Lawter, Inc. ("Lawter") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter's terms and conditions of sale. LAWTER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter's specifications. Nothing contained herein constitutes an offer for the sale of any product.