



Technical Data Sheet

# Pinerez<sup>®</sup> 2400M E

## *Modified ester of stabilized rosin*

### IMPORTANT CHARACTERISTICS:

**Pinerez<sup>®</sup> 2400M** is a medium to high softening point modified ester of stabilized rosin with good color and viscosity stability. **Pinerez 2400M** is intended for use in hot melt formulations for road marking.

### APPLICATIONS:

- Hot melt adhesives
- Road marking

### BENEFITS:

- Color and viscosity stable

### Typical Properties

Property	Value	Test Method / Standard
Softening Point (°C)	100	Ring & Ball
Acid Value (mg KOH/g)	14	Titration
Color	4	Gardner (50% Toluene)

Updated 10/09/14 NPH

For more information, please contact your sales or technical representative.

® and ™ Licensed trademarks of Lawter, Inc.

### DISCLAIMER

The information provided herein was believed by Lawter, Inc. ("Lawter") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter's terms and conditions of sale. LAWTER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter's specifications. Nothing contained herein constitutes an offer for the sale of any product.