

SETAPRINT [™] 2376 E

Phenolic Modified Rosin Resin

IMPORTANT CHARACTERISTICS:

Setaprint™ 2376 E is a highly soluble, medium low viscosity hard resin for offset.

Setaprint[™] **2376 E** has excellent pigment wetting properties and gives high gloss.

Setaprint™ 2376 **E** is combined with lower soluble resins to increase set speed.

Setaprint™ 2376 E is used in aromatic free inks and varnishes.

APPLICATIONS:

- Offset
- Grinding varnishes
- Sheetfed and gloss offset inks
- Aromatic free inks and varnishes
- Web Offset, Heatset and Coldset
- Letterpress

BENEFITS:

- Good pigment grinding
- · High gloss combined with fast setting
- Good flow
- Good gelling properties
- Low misting

Typical Properties

Property	Value	Unit	Test Method
Viscosity	37	Pa.s	Physica 23 °C, at 25 sec ⁻¹
(50 % in Test Oil 6/9)			LIMV2
Cloudpoint	134	°C	LIMR5
(10 % in Test Oil 6/9 af)			

Updated: March 19, 2012 by AdK

® and ™ Licensed trademarks of Lawter, Inc.

DISCLAIMER

The information provided herein was believed by Lawter, Inc. ("Lawter") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter's terms and conditions of sale. LAWTER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter's specifications. Nothing contained herein constitutes an offer for the sale of any product.