

Technical data sheet

# SETALIN V555C

# Linseed oil based alkyd resin

#### IMPORTANT CHARACTERISTICS:

**Setalin V 555 C** is a low medium viscous linseed based alkyd resin with good pigment wetting properties and good litho properties.

Grinding or flushing in **Setalin V 555 C** can develop more color strength and cleanliness than conventional wetting vehicles, while maintaining excellent flow characteristics. It is an outstanding pigment binder on most printable surfaces.

## **APPLICATIONS:**

- · Sheetfed offset ink
- · Webfed offset ink
- Wetting varnishes

#### **BENEFITS:**

- · Good pigment wetting
- Drying
- Fast setting
- High gloss
- Low bronzing
- Flow

## **Typical Properties**

Property	Value	Unit	Test Method
Viscosity	210	Seconds	G-H, End-End, 25℃
Colour	Max.12	Gardner	
Acid Value	Max.12	mg KOH/g	
Methanol Number	40	ml/5 g alkyd solution	
Oil length	70	%	Calculation

Former name: TERLON 5C

Updated 5/18/11 TM

#### ® and ™ Licensed trademarks of Lawter, Inc.

#### **DISCLAIMER**

The information provided herein was believed by Lawter, Inc. ("Lawter") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter's terms and conditions of sale. LAWTER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter's specifications. Nothing contained herein constitutes an offer for the sale of any product.