

ECO-REZ™ 9520 E**Rosin Resin****IMPORTANT CHARACTERISTICS:**

- **The ECO-REZ™ resins** provide greener chemistry, high performance and economic value all in one package.
- **The ECO-REZ™ resins** make it possible to develop a complete Phenol-Free sheetfed and heatset ink system.
- **ECO-REZ™ resins** contain >80% renewable content – significantly higher than modified phenolic.
- With **ECO-REZ™ resin technology** you are making a statement and commitment to a greener product line and progression toward a more sustainable print environment.
- **ECO-REZ™ 9520 E** exhibits medium solubility combined with a medium viscosity in vegetable oil systems, **ECO-REZ™ 9520 E** can be used in let down varnishes in combination with grinding varnishes based on **ECO-REZ™ 9500 E**.
- See for all kind of extra information our phenol formaldehyde free resin leaflets and presentations.

APPLICATIONS:

- *Offset*
- *Web Offset, Heatset and Coldset*
- *Sheetfed and Gloss Offset*
- *Let down varnishes*
- *Low odour inks and Over Print Varnishes*
- *Phenol-free and Formaldehyde free inks*

BENEFITS:

- *Low tack*
- *Excellent gel response*
- *Low yellowing and low odour*
- *Phenol free and Formaldehyde free*
- *Easy to de-ink*
- *Wider water window*
- *Excellent anti-misting properties*

Typical Properties

Property	Value	Unit	Test Method
Viscosity (50 % in Methyl ester of rapeseed oil)	21	Pa.s	Physica 23 °C, at 25 sec ⁻¹ LIMV2
Viscosity (40 % in Test Oil 6/9 ar blend)	40	Pa.s	Physica 23 °C, at 25 sec ⁻¹ LIMV2
Cloudpoint (10 % in Test Oil 6/9)	90	°C	LIMR5

Updated: February 16th 2011 by AdK

® and ™ Licensed trademarks of Lawter, Inc.

DISCLAIMER

The information provided herein was believed by Lawter, Inc. ("Lawter") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter's terms and conditions of sale. LAWTER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter's specifications. Nothing contained herein constitutes an offer for the sale of any product.