

FLEXONICTM W378 E

Polyethylene emulsion

IMPORTANT CHARACTERISTICS:

Flexonic™ W-378 E is an emulsion of high melting point polyethylene wax and does not contain APE.

Flexonic™ W-378 E is used as an additive in water based inks, coatings and over print varnishes, where improved slip, rub resistance, scratch resistance and/or block resistance are needed.

Flexonic™ W-378 E can be used as an additive to paper coatings, wood coatings, metal coatings, overprint varnishes, floor polish and other markets where slip and hardness are required, without significant degradation of gloss.

Addition levels range from 2 – 10%, depending on application requirements.

APPLICATIONS:

- Aqueous inks
- Aqueous coatings; paper, wood, metal, OPV and other applicable coatings

BENEFITS:

- Slip, rub resistance, scratch resistance and block resistance
- Minimal effect on gloss
- Excellent compatibility with acrylics & styrene acrylics

Typical Properties

Property	Value	Unit	Test Method / Standard
Solids	55	%	
Avarage Particle Size	6	μm	Malvern Mastersizer "S"

Updated: February 24, 2011 by AdK

® and ™ Licensed trademarks of Lawter, Inc.

DISCLAIMER

The information provided herein was believed by Lawter, Inc. ("Lawter") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter's terms and conditions of sale. LAWTER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter's specifications. Nothing contained herein constitutes an offer for the sale of any product.