



Technical Data Sheet

POLYSLIP™ VM 70 E

Solvent based wax dispersion

IMPORTANT CHARACTERISTICS:

Polyslip™ VM 70 E is a dispersion of a mix of a carnauba wax in isopropanol and solvent “150”.

Polyslip™ VM 70 E is used as a lubricant for solvent borne can coatings, 2-piece white and clear coats, gold lacquers and finishing varnishes.

Polyslip™ VM 70 E give excellent scratch resistance and excellent slip. **Polyslip™ VM 70 E** has good leveling properties and give no loss of gloss. Addition levels range from 1 – 5%, depending on application requirements.

APPLICATIONS:

- Solvent borne can coatings.
- 2-piece can white and clear coats
- Gold lacquers
- Finishing varnishes

BENEFITS:

- Excellent slip
- Excellent scratch resistance
- No loss of gloss
- Good leveling

Typical Properties

Property	Value	Unit	Test Method / Standard
Solids	20	%	
Average Particle size	4	µm	Grind gauge 0-25µm

Updated: February 22, 2011 by AdK

® and ™ Licensed trademarks of Lawter, Inc.

DISCLAIMER

The information provided herein was believed by Lawter, Inc. (“Lawter”) to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter’s terms and conditions of sale. LAWTER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter’s specifications. Nothing contained herein constitutes an offer for the sale of any product.