LAWTER™

Technical Data Sheet

POLYSLIP^{TM} VS 86 E

(rendered as) POLYSLIP^{TM} VS 86 E

Solvent based wax dispersion

IMPORTANT CHARACTERISTICS:

Polyslip™ VS 86 E is a dispersion of a mix of waxes in a mixture of solvents (n-butanol, methoxypropanol, solvent "150" and pine oil).

Polyslip™ VS 86 E is used as a lubricant for solvent borne can coatings, 2-piece white and clear coats, internal lacquers (2p & 3-p cans) and finishing varnishes.

Polyslip™ VS 86 E give excellent scratch resistance and excellent slip. **Polyslip™ VS 86 E** has good leveling properties and give no loss of gloss. Addition levels range from 1 – 5%, depending on application requirements.

APPLICATIONS:
- Solvent borne can coatings.
- 2-piece can white and clear coats
- Internal lacquers (2-p & 3-p cans)
- Finishing varnishes

Recommendation: best stored between 10 and 30 ⁰C

BENEFITS:
- Excellent slip
- Excellent scratch resistance
- No loss of gloss
- Good leveling

Typical Properties

Property	Value	Unit	Test Method / Standard
Solids	15	%	
Avarage Particle size	8	µm	Grind gauge 0-25µm

Updated: February 22, 2011 by AdK