



Technical Data Sheet

## Filtrez™ 3310 A Maleic Modified Rosin Ester

### IMPORTANT CHARACTERISTICS:

Filtrez™ 3310 A is a maleic modified rosin ester. Filtrez 3310 A is designed for the thermoplastic pavement marking industry, and it allows for less plasticizer in the finished application. Other possible applications include modifying nitrocellulose for lacquer in the coatings industry

### APPLICATIONS:

- Coatings
- Pavement marking

### BENEFITS:

- Great adhesion
- Reduced plasticizer requirement

### Typical Properties

Property	Value	Test Method / Standard
Melt Point:	121°C	Ring & Ball, degC BAX-QC-100
Acid Value:	38	BAX-QC-102
Viscosity:	318 cps.	Brookfield Thermosel Viscosity, cps. at 410°F (210°C), BAX-QC-162
Color:	6	Gardner Color (60% in toluene) BAX-QC-103

Updated 5/26/2015 TD

### Solubility Parameters:

Determined at 50% resin concentration

Class I Solvents:	8.9-9.7
Class II Solvents:	8.4-10.0
Class III Solvents	Insoluble

For more information, please contact your sales or technical representative.

® and ™ Licensed trademarks of Lawter, Inc.

### DISCLAIMER

The information provided herein was believed by Lawter, Inc. ("Lawter") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter's terms and conditions of sale. LAWTER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter's specifications. Nothing contained herein constitutes an offer for the sale of any product.