



Technical Data Sheet

Optilith™ AM A Anti-Misting Additive

IMPORTANT CHARACTERISTICS:

Optilith™ AM A is an anti-mist compound. **Optilith AM A** is a 95% non-volatile, high solids paste. **Optilith AM A** gives maximum reduction in misting without adversely effecting gloss or ink rheology. **Optilith AM A** is effective at 0.5 to 3% use levels.

APPLICATIONS:

- Heatset offset ink
- Sheetfed offset ink
- Metal deco, OPV

BENEFITS:

- Inhibits misting
- Minimal impact on tack and rheology
- Excellent gloss retention

Typical Properties

Property	Value	Test Method / Standard
Grind:	N-3	NPIRI Gage units (3% in ink) Method: BAX-QC-201
Peppering:	N-4	NPIRI Gage units (3% in ink) Method: BAX-QC-201
Appearance:	Off-white paste	
% Non-volatile:	95	Method: BAX-QC-195
Solvent Boiling Range:	212°F	
Weight/Gallon:	9.1 lbs	Method: BAX-QC-130

Updated 5/28/2015 JGC

For more information, please contact your sales or technical representative.

© and ™ Licensed trademarks of Lawter, Inc.

DISCLAIMER

The information provided herein was believed by Lawter, Inc. ("Lawter") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter's terms and conditions of sale. LAWTER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter's specifications. Nothing contained herein constitutes an offer for the sale of any product.