



Technical Data Sheet

Pinerez[®] 2260

Ester of stabilized rosin

IMPORTANT CHARACTERISTICS:

Pinerez[®] 2260 is a rosin ester of medium to high softening point. It has been specially treated to give low odor when incorporated in hot melt formulations. It is a pale resinous solid with good heat, color and viscosity stability.

APPLICATIONS:

- EVA Hot Melt Adhesive
 - Packaging, furniture.
- Solvent adhesive
 - Tape, construction

BENEFITS:

- Color and viscosity stability
- Good adhesion
- Compatible with a range of adhesive polymers e.g.: SIS, SBS, NR, EVA

Typical Properties

Property	Value	Test Method / Standard
Softening Point (°C)	100	Ring & Ball
Acid Value (mg KOH/g)	14	Titration
Color	5	Gardner (50% Toluene)

Updated 02/02/11 NPH

For more information, please contact your sales or technical representative.

® and ™ Licensed trademarks of Lawter, Inc.

DISCLAIMER

The information provided herein was believed by Lawter, Inc. ("Lawter") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter's terms and conditions of sale. LAWTER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter's specifications. Nothing contained herein constitutes an offer for the sale of any product.