

Pinerez® 2394 E

Pentaerythritol ester of stabilized rosin

IMPORTANT CHARACTERISTICS:

Pinerez® 2394 E is a light colored tackifier resin that is modified to exhibit good stability against oxidation, heat aging and ultra violet light. The typical use of **Pinerez 2394 E** is to improve tack and adhesion in a wide range of adhesives.

APPLICATIONS:

- EVA Hot Melt Adhesive
 - Packaging, bookbinding, furniture
- Pressure Sensitive Hot Melt Adhesive
 - Tape & Label
- Solvent Adhesive
 - Tape, construction
- Thermoplastic road marking

BENEFITS:

- Improved adhesion
- Good color stability
- Good viscosity stability
- Compatible with a range of adhesive
- Polymers e.g.: SIS, SBS, NR, EVA

Typical Properties

Property	Value	Test Method / Standard
Softening Point (°C)	105	Mettler Softening Point
Softening Point (°C)	98	Ring & Ball
Color	4	Gardner (50% Toluene)
Acid Value (mg KOH/g)	14	Titration

Updated 02/02/11 NPH

For more information, please contact your sales or technical representative.

® and ™ Licensed trademarks of Lawter, Inc.

DISCLAIMER

The information provided herein was believed by Lawter, Inc. ("Lawter") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter's terms and conditions of sale. LAWTER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter's specifications. Nothing contained herein constitutes an offer for the sale of any product.