

## Pinerez® 2490

### Ester of stabilized of rosin

**IMPORTANT CHARACTERISTICS:**

**Pinerez® 2490** is a light colored tackifier resin that is modified to exhibit good stability against oxidation, heat aging and ultra violet light. **Pinerez 2490** has a medium softening point. The typical use is to improve tack and adhesion in a wide range of adhesives

**APPLICATIONS:**

- EVA Hot Melt Adhesive
  - Packaging, bookbinding, furniture
- Pressure Sensitive Hot Melt Adhesive
  - Tape & Label
- Solvent Adhesive
  - Tape, construction

**BENEFITS:**

- Improved adhesion
- Higher cohesion
- Good color stability
- Good viscosity stability
- Compatibility with a range of adhesive
- Polymers e.g.: SIS, SBS, NR, EVA, PSA

**Typical Properties**

Property	Value	Test Method / Standard
Softening Point (°C)	90	Ring & Ball
Color	5	Gardner (50% Toluene)
Acid Value (mg KOH/g)	14	Titration

Updated 02/02/11 NPH

For more information, please contact your sales or technical representative.

® and ™ Licensed trademarks of Lawter, Inc.

**DISCLAIMER**

The information provided herein was believed by Lawter, Inc. ("Lawter") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter's terms and conditions of sale. LAWTER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter's specifications. Nothing contained herein constitutes an offer for the sale of any product.