

SETALIN™ V 454 E***Linseed oil based alkyd resin*****IMPORTANT CHARACTERISTICS:**

Setalin™ V 454 E is a medium viscous alkyd resin giving a low tack and fast setting.

APPLICATIONS:

- Offset,
- Web offset: Heatset and Coldset
- Letterpress and Screen inks
- Sheetfed
- Wetting and Letdown varnishes

BENEFITS:

- Tin free
- Fast setting
- Low tack
- Very good pigment wetting. High gloss
- Low bronzing
- Reduced water sensitivity
- Improved hold-out and reduced misting

Typical Properties

Property	Value	Unit	Test Method *
Viscosity	70	Pa.s	LIMV2
Colour	8	Gardner	LIMA5
Acid Value	12	mg KOH/g	LIMA1
Methanol Number	35	ml/5 grams alkyd solution	LIMA2
Oil length	63	%	
Appearance	Slightly hazy		Visual

Updated: November 2, 2015 by AdK

* Lawter Standard Test Method

® and ™ Licensed trademarks of Lawter, Inc.

DISCLAIMER

The information provided herein was believed by Lawter, Inc. ("Lawter") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter's terms and conditions of sale. LAWTER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter's specifications. Nothing contained herein constitutes an offer for the sale of any product.