Technical Data Sheet



PINEREZ™ 7016 E

PINEREZ™ 7016 E is a low viscosity liquid ester of rosin.

Application

PINEREZ™ 7016 E is used primarily to improve adhesion in water based flooring adhesives and complies with RAL-UZ 113.

Compatible with a range of polymers including VAE, acrylic and SBR

▲ Low VOC for EC1 adhesives▲ Complies with RAL-UZ 113

Low odor

Typical properties			
Property	Value	Unit	Test Method
Viscosity	1000	mPa.s	Brookfield (Sp. 5, 100rpm, 50°C)
Acid Value	12	mgKOH/g	Titration
Color	7	Gardner	50% in Toluene
Sustainability			
Bio-Renewable Content	62	%	Mass ratio
Carbon Footprint	-0.3	KgCO ₂ /Kg product	ISO 14040 Cradle to Gate

Updated February 24th 2025 by NPH

Packaging

PINEREZ™ 7016 E can be available in IBC, drums or in heated tank wagon.

Shelf life and storage conditions

Shelf life of the product is 12 months.

It is recommended to store IBCs & drums in a warehouse or undercover.

Disclaimer

The information provided herein was believed by Later, Inc. ("Lawter") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter's terms and conditions of sale.

LAWTER MAKES NO WARRANT, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY IMFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter's specifications. Nothing contained herein constitutes an offer for the sale of any product.

[®] and ™ Licensed trademarks of Lawter, Inc.