

PINEREZ™ 7053 E

PINEREZ™ 7053 E is a resin melt that includes a blend of rosin resins.

Application

PINEREZ™ 7053 E is used primarily to improve adhesion in water based flooring adhesives and complies with RAL-UZ 113.

- ▲ Compatible with a range of polymers including VAE, acrylic and SBR
- ▲ Improves adhesion and grab when formulated
- ▲ Low VOC for EC1 adhesives
- ▲ Complies with RAL-UZ 113
- ▲ Low odor

Typical properties

Property	Value	Unit	Test Method
Viscosity	1000	mPa.s	Brookfield (Sp. 27, 50rpm, 70°C)
Acid Value	70	mgKOH/g	Titration
Color	7	Gardner	50% in Toluene
Sustainability			
Bio-Renewable Content	71	%	Mass ratio
Carbon Footprint	-0.4	KgCO ₂ /Kg product	ISO 14040 Cradle to Gate

Updated January 1st 2025 by NPH

Packaging

PINEREZ™ 7053 E can be available in drums or in heated tank wagon.

Shelf life and storage conditions

Shelf life of the product is 12 months.

It is recommended to store drums in a warehouse or undercover.

® and ™ Licensed trademarks of Lawter, Inc.

Disclaimer

The information provided herein was believed by Lawter, Inc. ("Lawter") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter's terms and conditions of sale.

LAWTER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter's specifications. Nothing contained herein constitutes an offer for the sale of any product.