

PINEREX[™] 7016 C

PINEREX[™] 7016 C is a low viscosity liquid ester of rosin.

Application

PINEREX[™] 7016 C is used primarily to improve adhesion in water based flooring adhesives and complies with RAL-UZ 113.

- ▲ Improves adhesion and grab when formulated
- ▲ Low odor

- ▲ Compatible with a range of polymers including VAE, acrylic and SBR
- ▲ Complies with RAL-UZ 113

Typical properties

Property	Value	Unit	Test Method
Acid value	12	mgKOH/g	Titration
Viscosity	1000	mPa.s	Brookfield (Sp 5, 10rpm, 50°C)
Color	7	Gardner	50% Toluene

Updated April 30, 2025 by JH

Packaging

PINEREX[™] 7016 C is shipped in drums.

Shelf life and storage conditions

Shelf life from date of production is typically 12 months. It is recommended to store drums in a warehouse or undercover.

® and ™ Licensed trademarks of Lawter, Inc.

Disclaimer

The information provided herein was believed by Lawter, Inc. ("Lawter") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter's terms and conditions of sale. LAWTER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter's specifications. Nothing contained herein constitutes an offer for the sale of any product.