Technical Data Sheet



SETAPRINT™ M 6150

SETAPRINT™ M 6150 is a fumaric rosin ester with high ethanol and water viscosity and high melting point.

SETAPRINT™ M 6150 has good dispersability in alcohol and aqueous solutions.

Application

Emulsion Floor Polishes, Water-Alcohol Flexographic Inks

Δ	Good leveling
Δ	High gloss

Δ	Good film hardness
Δ	High melting point

Typical properties						
Property	Value	Unit	Test Method			
Acid Number	177	mg KOH/g	Titration			
Viscosity	L	Gardner-Holdt	60% NV Ethanol @ 25°C			
Melting Point	144	°C	Capillary			
Color	Max. 12	Gardner	60% NV Ethanol			
Sustainability						
Bio-Renewable Content	78	%	Mass ratio			

Updated May 21, 2025 by MA

Packaging

SETAPRINT™ M 6150 can be available as flakes in 25kg bags.

Shelf life and storage conditions

Shelf life from date of production is typically 12 months. The resin should be stored at temperatures below 30°C. If the resin is stored wrongly or for a longer period of time, an increase in viscosity is possible.

® and ™ Licensed trademarks of Lawter, Inc.

Disclaimer

The information provided herein was believed by Later, Inc. ("Lawter") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter's terms and conditions of sale.

LAWTER MAKES NO WARRANT, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY IMFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter's specifications. Nothing contained herein constitutes an offer for the sale of any product.