

## TURPENTINE

**TURPENTINE** is manufactured by distillation from *Elliottii* pine gum.

### Application

**TURPENTINE** is formulated solvent and thinners in the paint industry.

### Wetting agents

## Typical properties

Property	Value	Unit	Test Method
Color	75	APHA	---
Specific Weight	0.873	g/cm <sup>3</sup>	Pycnometry @ 20°C
Refractive Index	1.473	---	ABBE Refractometer @ 20°C
Optical Rotation	Levorotatory	---	---
Humidity	Traces	%	---
Beta Pinene	36	%(AR/AR)	GPC Capillary composition
Total Bicyclic Hydrocarbons	87	%(AR/AR)	GPC Capillary composition
Total Terpenic Alcohols	2.4	%(AR/AR)	GPC Capillary composition
<b>Sustainability</b>			
Bio-Renewable Content	100	%	Mass ratio

Updated 26 February 2025 by MA

### Packaging

**TURPENTINE** can be available as bulk in 20mT bulk.

### Shelf life and storage conditions

Shelf life of the product is 12 months.

® and ™ Licensed trademarks of Lawter, Inc.

#### Disclaimer

The information provided herein was believed by Lawter, Inc. ("Lawter") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Lawter are subject to Lawter's terms and conditions of sale.

LAWTER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY LAWTER, except that the product shall conform to Lawter's specifications. Nothing contained herein constitutes an offer for the sale of any product.